



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006

SDS # : 081150

**QUARTZ INEO EFFICIENCY
0W-30**

Date of the previous version: 2014-02-20

Revision Date: 2015-04-07

Version 3

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE
COMPANY/UNDERTAKING

1.1. Product identifier

Product name	QUARTZ INEO EFFICIENCY 0W-30
Number	8LB
Substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Motor oil.
------------------------	------------

1.3. Details of the supplier of the safety data sheet

Supplier	TOTAL UK LIMITED One Euston Square 40 Melton Street. London. NW1 2FD UNITED KINGDOM Tel: +44 (0)20 7339 8000 Fax: +44 (0)20 7339 8033
-----------------	--

For further information, please contact:

Contact Point	Specific Product Related Info : 01977 636200
E-mail Address	rm.gb-msds@total.co.uk

1.4. Emergency telephone number

00 33 149 00 00 49 (24h/24, 7d/7)
TOTAL UK Ltd: + 44 (0) 20 7339 8000
For Lubricants only: TOTAL Lubricants - +44 (0)1977 636200
For bitumen only: Total Bitumen +44 (0) 17 7272 9302

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008 ***

*For the full text of the H-Statements mentioned in this Section, see Section 2.2. ****

Classification***

The product is classified as dangerous in accordance with Regulation (EC) No. 1272/2008***



SDS # : 081150

QUARTZ INEO EFFICIENCY 0W-30

Revision Date: 2015-04-07

Version 3

Chronic aquatic toxicity - Category 4*** - (H413)***

DIRECTIVE 67/548/EEC or 1999/45/EC

For the full text of the R-phrases mentioned in this Section, see Section 16.

The substance/mixture is classified as dangerous in accordance with Directive(s) 67/548/EEC with amendments and/or 1999/45/EC with amendments

Classification

R52/53 ***

2.2. Label elementsLabelled according to **REGULATION (EC) No 1272/2008*******Hazard Statements *****

H413 - May cause long lasting harmful effects to aquatic life***

Precautionary statements

P501 - Dispose of contents/container to an approved waste disposal plant***

2.3. Other hazards**Physical-Chemical Properties** Contaminated surfaces will be extremely slippery.**Environmental properties** Should not be released into the environment.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture**Chemical nature** The product is made from refined mineral base oils and synthetic oils.

Chemical Name	EC-No	REACH Registration Number	CAS-No	Weight %	Classification (Dir. 67/548)	GHS Classification
1-dodecene, trimer, hydrogenated***	417-070-7	01-0000016388-62	151006-62-1	<50	R53	Aquatic Chronic 4 (H413)
Distillates (petroleum), hydrotreated heavy paraffinic***	265-157-1	01-2119484627-25	64742-54-7	<30	-	Asp. Tox. 1 (H304)
1-dodecene, homopolymer, hydrogenated***	417-070-7	01-0000016388-62	151006-63-2	<10	R53	Aquatic Chronic 4 (H413)
bis(nonylphenyl)amine***	253-249-4	01-2119488911-28	36878-20-3	<1.5	R53	Aquatic Chronic 4 (H413)
2,6-di-tert-butylphenol***	204-884-0	01-2119490822-33	128-39-2	<0.25	Xi;R38 N;R50-53	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) Skin Irrit. 2 (H315)



SDS # : 081150

QUARTZ INEO EFFICIENCY 0W-30

Revision Date: 2015-04-07

Version 3

Phenol, dodecyl-, branched***	310-154-3	01-2119513207-49	121158-58-5	<0.15	Xi;R36/38 N;R50-53 Repr.Cat.3;R62	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) Eye Irrit. 2 (H319) Repr. 2 (H361f) Skin Irrit. 2 (H315)
Diphenylamine***	204-539-4	no data available	122-39-4	<0.15	T; R23/24/25 R33 N; R50-53	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT RE 2 (H373) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids.
Skin contact	Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse.
Inhalation	Move to fresh air.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control centre immediately.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact	Not classified.
Skin contact	Not classified. May produce an allergic reaction.***
Inhalation	Not classified. Inhalation of vapours in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

Section 5: FIRE-FIGHTING MEASURES



SDS # : 081150

QUARTZ INEO EFFICIENCY 0W-30

Revision Date: 2015-04-07

Version 3

5.1. Extinguishing media

Suitable extinguishing media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

5.3. Precautions for fire-fighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up Dam up. Contain spillage, and then collect with non-combustable absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Personal protective equipment See Section 8 for more detail.

Waste treatment See section 13.

Section 7: HANDLING AND STORAGE



SDS # : 081150

QUARTZ INEO EFFICIENCY 0W-30

Revision Date: 2015-04-07

Version 3

7.1. Precautions for safe handling

Advice on safe handling	When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.
Prevention of fire and explosion	Take precautionary measures against static discharges: Ground/bond containers, tanks and transfer/receiving equipment.
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions	Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Preferably keep in the original container. Otherwise, reproduce all the statutory information from the labels onto the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.
Materials to avoid	Strong oxidising agents.

7.3. Specific use(s)

Specific use(s) No information available.***

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parametres

Exposure limits Mineral oil mist:
USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

Chemical Name	European Union	The United Kingdom	Ireland
Diphenylamine*** 122-39-4		STEL 20 mg/m ³ TWA 10 mg/m ³	TWA 10 mg/m ³ STEL 20 mg/m ³

Legend

See section 16

DNEL Worker (Industrial/Professional)***

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects



SDS # : 081150

QUARTZ INEO EFFICIENCY 0W-30

Revision Date: 2015-04-07

Version 3

Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7				5.4 mg/m ³ /8h (aerosol - inhalation)
bis(nonylphenyl)amine*** 36878-20-3			0.62 mg/kg bw/day Dermal 4.37 mg/m ³ Inhalation	
2,6-di-tert-butylphenol*** 128-39-2			2.77 mg/kg bw/day Dermal 19.6 mg/m ³ Inhalation	
Phenol, dodecyl-, branched*** 121158-58-5	166 mg/kg bw/day Dermal 44.18 mg/m ³ Inhalation		0.25 mg/kg bw/day Dermal 1.7621 mg/m ³ Inhalation	

DNEL Consumer***

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7				1.2 mg/m ³ /24h (aerosol - inhalation)
bis(nonylphenyl)amine*** 36878-20-3			0.31 mg/kg bw/day Dermal 1.09 mg/m ³ Inhalation 0.31 mg/kg bw/day Oral	
2,6-di-tert-butylphenol*** 128-39-2			1.67 mg/kg bw/day Oral 5.8 mg/m ³ Inhalation	
Phenol, dodecyl-, branched*** 121158-58-5	50 mg/kg bw/day Dermal 13.26 mg/m ³ Inhalation 1.26 mg/kg bw/day Oral		0.075 mg/kg bw/day Dermal 0.79 mg/m ³ Inhalation 0.075 mg/kg bw/day Oral	

Predicted No Effect Concentration (PNEC) ***

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
bis(nonylphenyl)amine*** 36878-20-3	0.1 mg/l fw 0.01 mg/l mw 1 mg/l or	132000 mg/kg dw fw 13200 mg/kg dw mw	263000 mg/kg dw		1 mg/l	
2,6-di-tert-butylphenol*** 128-39-2	0.00045 mg/l fw 0.000045 mg/l mw 0.0045 mg/l or	0.196 mg/kg dw fw 0.0196 mg/kg dw mw	0.0389 mg/kg dw		10 mg/l	
Phenol, dodecyl-, branched*** 121158-58-5	0.000074 mg/l fw 0.0000074 mg/l mw 0.00037 mg/l or	0.226 mg/kg fw dw 0.0266 mg/kg mw dw	0.118 mg/kg dw		100 mg/l	4 mg/kg food

8.2. Exposure controls**Occupational Exposure Controls**



SDS # : 081150

QUARTZ INEO EFFICIENCY 0W-30

Revision Date: 2015-04-07

Version 3

Engineering measures	Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.
Personal protective equipment	
General Information	If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P2. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.***
Eye protection	If splashes are likely to occur, wear: Safety glasses with side-shields.
Skin and body protection	Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.
Hand protection	Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves.

Environmental exposure controls

General Information The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Colour	yellow		
Physical state @20°C	Liquid		
Odour	characteristic		
Property	Values	Remarks	Method
pH		Not applicable	
Boiling point/boiling range		Not applicable	
Flash point	> 200 °C > 392 °F		
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
Vapour pressure		No information available	
Vapour density		No information available	
Density	850 kg/m ³	@ 15 °C	



SDS # : 081150

QUARTZ INEO EFFICIENCY 0W-30

Revision Date: 2015-04-07

Version 3

Water solubility		Insoluble	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		No information available	
Viscosity, kinematic	64 mm ² /s	@ 40 °C	ISO 3104
Explosive properties	Not explosive		
Oxidising properties	Not applicable		
Possibility of hazardous reactions	Not applicable		

9.2. Other information

No information available***

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

General Information No information available.***

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions None under normal processing.

10.4. Conditions to Avoid

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products None under normal use.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact . Not classified. May produce an allergic reaction.***

SDS # : 081150

QUARTZ INEO EFFICIENCY 0W-30

Revision Date: 2015-04-07

Version 3

Eye contact	. Not classified.
Inhalation	. Not classified. Inhalation of vapours in high concentration may cause irritation of respiratory system.
Ingestion	. Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy paraffinic***	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
1-dodecene, homopolymer, hydrogenated***	LD50 > 5000 mg/kg (Rat)	LD50 > 2000 mg/kg (Rat)	LC50 (4h) > 5.06 mg/l (Rat - aerosol)
bis(nonylphenyl)amine***	LD50 > 5000 mg/kg (Rat - OECD 401)	LD50 > 2000 mg/kg (Rat - OECD 402)	
2,6-di-tert-butylphenol***	> 5000 mg/kg (Rat)	LD50 > 2000 mg/kg (Rabbit)	
Phenol, dodecyl-, branched***	LD50 2700 mg/kg (Rat)	LD50 > 3160 mg/kg (Rat)	
Diphenylamine***	= 1165 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	

Sensitisation

Sensitisation Not classified as a sensitizer.

Specific effects

Carcinogenicity This product is not classified carcinogenic. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

Chemical Name	European Union
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7	-

Mutagenicity This product is not classified as mutagenic.
Reproductive toxicity This product does not present any known or suspected reproductive hazards.

Chemical Name	European Union
Phenol, dodecyl-, branched*** 121158-58-5	Repr. 2 (H361f)

Repeated Dose Toxicity

Subchronic Toxicity No information available.

Target Organ Effects (STOT)

Target Organ Effects (STOT) No information available.

Other information



SDS # : 081150

QUARTZ INEO EFFICIENCY 0W-30

Revision Date: 2015-04-07

Version 3

Other adverse effects

Characteristic skin lesions (oil blisters) may develop following prolonged and repeated exposures (contact with contaminated clothing).

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.***

Acute aquatic toxicity - Product Information

No experimental data available .

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)***	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
1-dodecene, homopolymer, hydrogenated*** 151006-63-2	EL50 (72h) > 1000 mg/l (Scenedesmus capricornutum)	EL50(48h) >1000 mg/l (Daphnia magna)	LC50(96h) > 1000 mg/l (Oncorhynchus mykiss)	
bis(nonylphenyl)amine*** 36878-20-3	EC50 (72h) > 100 mg/l (Desmodesmus subspicatus - OECD 201)	EC50 (48h) > 100 mg/l (Daphnia magna - OECD 202)	LC50 (96h) > 100 mg/l (Brachyanio rerio - OECD 203)	
2,6-di-tert-butylphenol*** 128-39-2	EC50 (72h) 1.2 mg/l	EC50 (48h) = 0.45 mg/L Daphnia magna	LC50(96h) 1 mg/l (fish)	
Phenol, dodecyl-, branched*** 121158-58-5	EbC50 (72h) 0.15 mg/l (Scenedesmus subspicatus - OECD 201)	EC50(48h) 0.037 mg/l (Daphnia magna - static - OECD 202)	EL50(96h) 40 mg/l Pimephales promelas semi-static (OECD 203)	
Diphenylamine*** 122-39-4	EC50 (72h) = 1.5 mg/l Scenedesmus subspicatus	EC50 (48h) 1.69 - 2.46 mg/L Daphnia magna	LC50 (96h) 3.47-4.14 mg/L Pimephales promelas (flow-through)	EC50 = 4.77 mg/L 30 min EC50 = 2.81 mg/L 5 min EC50 = 3.46 mg/L 15 min

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)***	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
1-dodecene, homopolymer, hydrogenated*** 151006-63-2		NOELR(21d) 125 mg/l (Daphnia magna)		



SDS # : 081150

QUARTZ INEO EFFICIENCY 0W-30

Revision Date: 2015-04-07

Version 3

2,6-di-tert-butylphenol*** 128-39-2			NOEC (28d) 0.3 mg/l (fish)	
Phenol, dodecyl-, branched*** 121158-58-5		NOEC(21d) 0.0037 mg/l (Daphnia magna - semi-static - OECD 211)		

Effects on terrestrial organisms

No information available.

12.2. Persistence and Degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information

No information available.

logPow

No information available

Component Information

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic*** - 64742-54-7	-
1-dodecene, homopolymer, hydrogenated*** - 151006-63-2	6.6
bis(nonylphenyl)amine*** - 36878-20-3	7.7
2,6-di-tert-butylphenol*** - 128-39-2	4.48
Phenol, dodecyl-, branched*** - 121158-58-5	7.14
Diphenylamine*** - 122-39-4	3.4

12.4. Mobility in soil

Soil

Given its physical and chemical characteristics, the product generally shows low soil mobility.

Air

Loss by evaporation is limited.

Water

Insoluble. The product spreads on the surface of the water.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

No information available.

12.6. Other adverse effects

General Information

No information available.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods



SDS # : 081150

QUARTZ INEO EFFICIENCY 0W-30

Revision Date: 2015-04-07

Version 3

Waste from residues / unused products	Should not be released into the environment. Do not empty into drains. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. Where possible recycling is preferred to disposal or incineration. After use, this oil must be sent to a licensed waste oil facility. Incorrect disposal of used oil poses a risk to the environment. Mixture with other waste types such as solvents, brake- and cooling liquids is forbidden.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
EWC Waste Disposal No	The following Waste Codes are only suggestions: 13 02 06. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

Section 14: TRANSPORT INFORMATION

<u>ADR/RID</u>	not regulated
<u>IMDG/IMO</u>	not regulated
<u>ICAO/IATA</u>	not regulated
<u>ADN</u>	not regulated

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

International Inventories **No information available*****

Further information

No information available***

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available



SDS # : 081150

QUARTZ INEO EFFICIENCY 0W-30

Revision Date: 2015-04-07

Version 3

15.3. National regulatory information

The United Kingdom

- Avoid exceeding occupational exposure limits (see section 8).

Ireland

- Avoid exceeding occupational exposure limits (see section 8).

Section 16: OTHER INFORMATION

Full text of R-phrases referred to under sections 2 and 3

R33 - Danger of cumulative effects

R38 - Irritating to skin

R53 - May cause long-term adverse effects in the aquatic environment***

R23/24/25 - Toxic by inhalation, in contact with skin and if swallowed.

R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment***

Full text of H-Statements referred to under sections 2 and 3

H301 - Toxic if swallowed

H304 - May be fatal if swallowed and enters airways

H311 - Toxic in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H331 - Toxic if inhaled

H361f - Suspected of damaging fertility

H373 - May cause damage to the kidneys/liver/eyes/brain/digestive system/central nervous system through prolonged or repeated exposure if swallowed

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H413 - May cause long lasting harmful effects to aquatic life***

Abbreviations, acronyms

Legend Section 8

TWA: Time Weight Average

STEL: Short Time Exposure Limit

+ Sensitiser

** Hazard Designation

M: Mutagen

*

C:

R:

Skin designation

Carcinogen

Toxic to reproduction

Revision Date: 2015-04-07

Revision Note *** Indicates updated section.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006



SDS # : 081150

QUARTZ INEO EFFICIENCY 0W-30

Revision Date: 2015-04-07

Version 3

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of Safety Data Sheet