

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS # : 30804

FLUIDE AT 42

Date of the previous version: 2015-03-31

Revision Date: 2016-11-03

Version 2.01

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	FLUIDE AT 42
Number	0DD
Substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Transmission fluid.

1.3. Details of the supplier of the safety data sheet

Supplier	TOTAL LUBRIFIANTS 562 Avenue du Parc de L'ile 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00 For: +22 (0)1 41 35 94 71
	Fax: +33 (0)1 41 35 84 71

For further information, please contact:

Contact Point	HSE
E-mail Address	rm.msds-lubs@total.com

1.4. Emergency telephone number

Emergency telephone: +44 1235 239670

France - ORFILA (INRS) Tél : +33 (0)1 45 42 59 59

In France : - PARIS : Hôpital Fernand Widal 200, rue du Faubourg Saint-Denis 75475 Paris Cédex 10, Tel : 01.40.05.48.48. -MARSEILLE : Hopital Salvator, 249 bd Ste Marguerite 13274 Marseille cedex 5, Tel : 04.91.75.25.25. - LYON : Hopital Edouard Herriot, 5 place d'Arsonvol, 69437 Lyon cedex 3, Tel : 04.72.11.69.11. - NANCY : Hopital central, 29 Av du Mal De Lattre de Tassigny, 54000 Nancy, Tel : 03.83.32.36.36 ou le SAMU : Tel (15)

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008 ***

For the full text of the H-Statements mentioned in this Section, see Section 2.2.***

Classification

The product is not classified as dangerous according to Regulation (EC) No. 1272/2008***



FLUIDE AT 42

Revision Date: 2016-11-03

Version 2.01

2.2. Label elements

Labelled according to

REGULATION (EC) No 1272/2008***

Signal Word None***

Hazard Statements None***

Precautionary Statements None***

Supplemental Hazard Statements EUH210 - Safety data sheet available on request***

EUH208 - Contains Alkoxylated long chain alkylamine. May produce an allergic reaction***

2.3. Other hazards

Physical-Chemical PropertiesContaminated surfaces will be extremely slippery.***Environmental propertiesShould not be released into the environment.***

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture

Chemical Name	EC-No	REACH registration No	CAS-No	Weight %	Classification (Reg. 1272/2008)
Distillates (petroleum), hydrotreated light paraffinic***	265-158-7***	01-2119487077-29	64742-55-8	50-<60	Asp. Tox. 1 (H304)
Methacrylate copolymer***	-	-	^	5-<10	Eye Irrit. 2 (H319)
Alkoxylated long chain alkylamine***	-	no data available	۸	0.25-<1	Skin Corr. 1B (H314) Skin Sens. 1 (H317) Acute Tox. 4 (H302) Aquatic Chronic 3 (H412)

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR



SDS # : 30804	FLUIDE AT 42		
	Revision Date: 2016-11-03 Version 2.0		
	EMERGENCY MEDICAL CARE.***		
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids.***		
Skin contact	Remove contaminated clothing and shoes. Wash skin with soap and water. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. Take victim immediately to hospital.***		
Inhalation	Move to fresh air.		
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.***		
4.2. Most important symp	otoms and effects, both acute and delayed		
Eye contact	Not classified.		
Skin contact	Not classified. May produce an allergic reaction.		
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.		
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.		
4.3. Indication of immedi	ate medical attention and special treatment needed, if necessary		
Notes to physician	Treat symptomatically.		
Section 5: FIRE-FIGHTING	MEASURES		
5.1. Extinguishing media	_		
Suitable Extinguishing Media	Carbon dioxide (CO 2). ABC powder. Foam. Water spray or fog.***		
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.		
5.2. Special hazards aris	ing from the substance or mixture		
Special Hazard	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.		

5.3. Advice for fire-fighters

Special protective equipment for fire-fighters	Wear self-contained breathing apparatus and protective suit.
Other information	Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.



FLUIDE AT 42

Revision Date: 2016-11-03

Version 2.01

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information

Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.***

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.***

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.***

6.4. Reference to other sections

Personal Protective Equipment	See Section 8 for more detail.	
Waste treatment	See section 13.	

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handlingWhen using, do not eat, drink or smoke. For personal protection see section 8. Use only in
well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes
and clothing.***Prevention of fire and explosionTake precautionary measures against static discharges. Ground/bond containers, tanks
and transfer/receiving equipment.***Hygiene measuresEnsure the application of strict rules of hygiene by the personnel exposed to the risk of
contact with the product. Regular cleaning of equipment, work area and clothing is
recommended. Wash hands before breaks and immediately after handling the product. Do
not use abrasives, solvents or fuels. Do not dry hands with rags that have been
contaminated with product. Do not put product contaminated rags into workwear pockets.***

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage
conditionsKeep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep
container tightly closed. Keep preferably in the original container. Otherwise reproduce all
indication of the regulation label on the new container. Do not remove the hazard labels of
the containers (even if they are empty). Design the installations in order to avoid accidental
emissions of product (due to seal breakage, for example) onto hot casings or electrical



SDS # : 30804	FLUIDE AT 42		
	Revision Date: 2016-11-03	Version 2.01	
	contacts. Protect from frost, heat and sunlight. Protect from moisture.***		
Materials to Avoid	Strong oxidizing agents.***		
7.3. Specific end uses			
Specific use(s)	No information available.		
Section 8: EXPOSURE CON	ITROLS/PERSONAL PROTECTION		
8.1. Control parameters			
Exposure limits	Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 m (TLV) TWA 5 mg/m³ (highly refined)	ng/m³, ACGIH	
Legend	See section 16		

Derived No Effect Level (DNEL)

DNEL Worker (Industrial/Professional)***

DIVEL WOIKEI (IIIuustila	in rolessional)			
Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), hydrotreated light paraffinic*** 64742-55-8				5.4 mg/m³/8h (aerosol - inhalation)
DNEL Consumer***				
Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), hydrotreated light paraffinic***				1.2 mg/m ³ /24h (aerosol - inhalation)

64742-55-88.2.Exposure controls

Occupational Exposure Controls

Engineering Measures	Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.
Personal Protective Equipment	
General Information	If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN



SDS # : 30804	FLUIDE AT 42	
	Revision Date: 2016-11-03	Version 2.01
	14387), Type A/P1. The use of breathing apparatus must comply strictly wir manufacturer's instructions and the regulations governing their choices and	
Eye Protection	If splashes are likely to occur, wear:. Safety glasses with side-shields.	
Skin and body protection	Protective gloves, Long sleeved clothing, Protective shoes or boots.	
Hand Protection	Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. In case of pro with the product, it is recommended to wear gloves complying with EN 420 standards, protecting at least for 480 minutes and having a thickness of 0,3 These values are indicative only. The level of protection is provided by the glove, its technical characteristics, its resistance to the chemicals to be han appropriateness of its use and its replacement frequency.***	and EN 374 38 mm at least. material of the

Environmental exposure controls

General Information

The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Color Physical State @20°C Odor Odor Threshold		limpid*** beige To red*** liquid*** Characteristic*** No information available***	
<u>Property</u> pH	Values	Remarks Not applicable***	Method
Melting point/range	***	Not applicable***	
Boiling point/boiling range		No information available***	
Flash point ***	186*** °C*** 367*** °F***		Cleveland Open Cup (COC)*** Cleveland Open Cup (COC)***
Evaporation rate Flammability Limits in Air		No information available*** No information available	
upper ***	***	No information available***	***
Lower ***	***	No information available***	***
Vapor Pressure Vapor density		No information available*** No information available***	
Relative density ***	*** 0.840*** -*** 0.890***	@ 15 °C ***	***
Density	840*** - *** 890*** kg/m ^{3***}	@ 15 °C***	
Water solubility	0	Insoluble***	
Solubility in other solvents		No information available***	
logPow Autoignition temperature		No information available*** No information available***	



SDS # : 30804	FLUI		
	Revision I	Date: 2016-11-03	Version 2.01
Decomposition temperature Viscosity, kinematic ***	*** *** 37*** mm2/s***	No information available*** @ 40 °C ***	*** ISO 3104 ***
Explosive properties Oxidizing Properties Possibility of hazardous reactions	Not explosive*** Not applicable*** No information availab	le***	
9.2. Other information			
Freezing Point	***	No information available***	
Section 10: STABILITY AND	REACTIVITY		
10.1. Reactivity			
General Information	No information availab	le.***	
10.2. Chemical stability			
Stability	Stable under recomme	nded storage conditions.	
10.3. Possibility of hazarde	ous reactions		
Hazardous Reactions	None under normal pro	ocessing.	
10.4. Conditions to Avoid			
Conditions to Avoid	Heat (temperatures ab	ove flash point), sparks, ignition p	ooints, flames, static electricity.***
10.5. Incompatible materia	als_		
Materials to Avoid	Strong oxidizing agent	S.***	
10.6. Hazardous Decompo	sition Products		
Hazardous Decomposition Product			ermolysis may produce gases of e, various hydrocarbons, aldehydes
Section 11: TOXICOLOGICA	L INFORMATION		
11.1. Information on toxic	ological effects		
Acute toxicity Local effects Produ	ct Information		
Skin contact Eve contact	. Not classified. May p . Not classified.	roduce an allergic reaction.	



FLUIDE AT 42

Revision Date: 2016-11-03

Version 2.01

Ingestion	respiratory system. . Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
ATEmix (oral)	7,421.00*** mg/kg***
ATEmix (dermal)	7,421.00*** mg/kg***
ATEmix (inhalation-dust/mist)	7.60*** mg/l***
ATEmix (inhalation-vapor)	98.10*** mg/l***

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated light paraffinic***	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
Alkoxylated long chain alkylamine***	LD50 1350 mg/kg (Rat)	, , , , , , , , , , , , , , , , , , , ,	LC50 (1h) 220 ppm (Rat - Vapor)
Sensitization		•	·
Sensitization	Not classified as a sensitizer.	Contains sensitizer(s). May pro	oduce an allergic reaction.
Specific effects			
Carcinogenicity Mutagenicity Reproductive toxicity	This product is not classified c This product is not classified a This product does not present	5	ductive hazards.
Repeated Dose Toxicity			
Subchronic toxicity	No information available.		
Target Organ Effects (STOT)			
Target Organ Effects (STOT)	No information available.		
Other information			
Other adverse effects	No information available.		
Section 12: ECOLOGICAL IN	FORMATION		

12.1. Toxicity

Not classified.

Acute aquatic toxicity - Product Information

No information available.***

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum),	EL50 (72h) > 100 mg/l	EL50 (48h) > 10000 mg/L	LL50 (96h) > 100 mg/L	



FLUIDE AT 42

Revision Date: 2016-11-03

Version 2.01

hydrotreated light	(Pseudokirchneriella	(Daphnia magna - OCDE	(Oncorhynchus mykiss -	
paraffinic***	subcapitata - OCDE 201)	202)	OCDE 203)	
64742-55-8				

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated light paraffinic*** 64742-55-8		NOEL (21d) 10 mg/l (Daphnia magna - OCDE 211)	NOEL (14/28d) >1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	

Effects on terrestrial organisms

No information available.**

12.2. Persistence and degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information	No information available.***
logPow Component Information	No information available*** No information available.***
12.4. Mobility in soil	

SoilGiven its physical and chemical characteristics, the product generally shows low soil
mobility.***AirLoss by evaporation is limited.***WaterInsoluble. The product spreads on the surface of the water.***12.5.Results of PBT and vPvB assessmentPBT and vPvB assessmentNo information available.

12.6. Other adverse effects

General Information

No information available.***

Section 13: DISPOSAL CONSIDERATIONS



SDS # : 30804	FLUIDE AT 42		
	Revision Date: 2016-11-03	Version 2.01	
13.1. Waste treatment m	ethods		
Waste from Residues / Unused Products	Dispose of in accordance with the European Directives on w After use, this oil must be sent to a licensed waste oil facility poses a risk to the environment. Mixture with other waste typ and cooling liquids is forbidden.	. Incorrect disposal of used oil	
Contaminated packaging	Empty containers should be taken to an approved waste har disposal.***	ndling site for recycling or	
EWC Waste Disposal No.	The following Waste Codes are only suggestions:. 13 01 10. Waste Catalogue, Waste Codes are not product specific, but codes should be assigned by the user based on the applicat used.***	t application specific. Waste	
Section 14: TRANSPORT I	NFORMATION		
ADR/RID	Not regulated		

ADR/RID	Hotrogulatou
IMDG/IMO	Not regulated
ICAO/IATA	Not regulated
ADN	Not regulated

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Further information

No information available

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available

Section 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3 H302 - Harmful if swallowed H304 - May be fatal if swallowed and enters airways



FLUIDE AT 42

Revision Date: 2016-11-03

Version 2.01

H314 - Causes severe skin burns and eye damage H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H412 - Harmful to aquatic life with long lasting effects*** Abbreviations, acronyms ACGIH = American Conference of Governmental Industrial Hygienists bw = body weight bw/day = body weight/day EC x = Effect Concentration associated with x% response GLP = Good Laboratory Practice IARC = International Agency for Research of Cancer LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals LL = Lethal Loading NIOSH = National Institute of Occupational Safety and Health NOAEL = No Observed Adverse Effect Level NOEC = No Observed Effect Concentration NOEL = No Observed Effect Level OECD = Organization for Economic Co-operation and Development OSHA = Occupational Safety and Health Administration UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material DNEL = Derived No Effect Level PNEC = Predicted No Effect Concentration dw = dry weight fw = fresh water mw = marine water or = occasional release Legend Section 8 TWA: Time Weight Average STEL: Short Time Exposure Limit PEL: Permissible exposure limit **REL: Recommended exposure limit TLV: Threshold Limit Values** Skin designation Sensitizer + ** Hazard Designation C: Carcinogen M: Mutagen R٠ Toxic to reproduction

 Revision Date:
 2016-11-03

 Revision Note
 *** Indicates updated section.

 This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.



FLUIDE AT 42

Revision Date: 2016-11-03

Version 2.01

End of the Safety Data Sheet