

Mopar International - Lubricant and Chemical Cross Reference Chart

Category	NEW Mopar International Part Number	Previous US Part Number	Previous International Part Number	Product	Product Description	MS-SPEC	Unit	MSQ
AUTOMATIC TRANSMISSION FLUIDS	68218054GA	68044406MA	68087385EA	ATF +4®	The approved automatic transmission fluid for all vehicles factory filled with ATF+4.	MS-9602	208 Liter Drum	1 Drum
AUTOMATIC TRANSMISSION FLUIDS	68218058GA	05013458AA	05103531EA/ 05013458GA	ATF +4®	The approved automatic transmission fluid for all vehicles factory filled with ATF+4.	MS-9602	5 Liter Bottle	3 Bottles
AUTOMATIC TRANSMISSION FLUIDS	68218057GA	05013457AA	05103527EA/ 05013457GA	ATF +4®	The approved automatic transmission fluid for all vehicles factory filled with ATF+4.	MS-9602	0.946 Liter Bottle	12 Bottles
AUTOMATIC TRANSMISSION FLUIDS	05191185GB	05191185AA	68004942EA	CVTF+4 TRANSMISSION FLUID	Mopar® CVT fluid is specially formulated for Constant Variable Transmission in PM/MK body.		5 Liter Bottle	3 Bottles
AUTOMATIC TRANSMISSION FLUIDS	05191184GA	05191184AA	68004937EA	CVTF+4 TRANSMISSION FLUID	Mopar® CVT fluid is specially formulated for Constant Variable Transmission in PM/MK body.		0.946 Liter Bottle	12 Bottles
AUTOMATIC TRANSMISSION FLUIDS	68218925GA	68157995AB	n/a	ZF 8 & 9 SPEED ATF®	Formulated as a high quality fluid specifically for the ZF 8HP45 & ZF 9HP45 transmission used in Chrysler Group LLC vehicles. Approved by Chrysler Engineering to ensure smooth and quiet operation. Provides superior lubrication to reduce wear. Meets ZF specifications.	8/9 ATF	0.946 Liter Bottle	12 Bottles
COOLANT	04267020GC	04267020AC	n/a	ANTIFREEZE/COOLANT 3-YEAR FORMULA - EMBITTERED	Ethylene glycol based three-year formulation to prevent freeze-up and boil-over while inhibiting corrosion. Only for vehicles factory filled with three-year coolant.	MS-7170	3.785 Liter Bottle	4 Bottles
COOLANT	68048953GB	68048953AB	05103532EC/ 68024164EB	CONCENTRATE ANTIFREEZE/COOLANT 5-YEAR/100,000 MILE -- EMBITTERED	Ethylene glycol-based five-year formulation to prevent freeze-up and boil-over while inhibiting corrosion. Only for vehicles factory filled with 5-year/100,000-mile coolant.	MS-9769G	3.785 Liter Bottle	4 Bottles
COOLANT	68163848GA	68163848AA	n/a	CONCENTRATE ANTIFREEZE/COOLANT 10 YEAR/150,000 MILE - EMBITTERED	Ethylene glycol based formulation to prevent freeze-up and boil-over while inhibiting corrosion. Must not be mixed with any non-conforming antifreeze. OAT (Organic Additive Technology). Developed for newvehicle technologies.	MS-12106	3.785 Liter Bottle	4 Bottles
COOLANT	68163849GA	68163849AA	n/a	50/50 PREDILUTED ANTIFREEZE/COOLANT 10 YEAR/150,000 MILE - EMBITTERED	Do not add water. Ethylene glycol based formulation to prevent freeze-up and boilover while inhibiting corrosion. Must not be mixed with any non-conforming antifreeze. OAT (Organic Additive Technology). Developed for new vehicle technologies.	MS-12106	3.785 Liter Bottle	4 Bottles
ENGINE OILS	68218950GA	n/a	n/a	SAE 0W-20 MOPAR® ENGINE OIL, full synthetic	Rating: API SN, Energy Conserving, ILSAC GF-5. Contains special protective additives for superior engine protection. Approved to service all engines that require SAE 0W-20 engine oils.	MS-6395	0.946 Liter Bottle	12 Bottles
ENGINE OILS	68218951GA	n/a	n/a	SAE 0W-20 MOPAR® ENGINE OIL, full synthetic	Rating: API SN, Energy Conserving, ILSAC GF-5. Contains special protective additives for superior engine protection. Approved to service all engines that require SAE 0W-20 engine oils.	MS-6395	5 Liter Bottle	3 Bottles
ENGINE OILS	68218952GA	n/a	n/a	SAE 0W-20 MOPAR® ENGINE OIL, full synthetic	Rating: API SN, Energy Conserving, ILSAC GF-5. Contains special protective additives for superior engine protection. Approved to service all engines that require SAE 0W-20 engine oils.	MS-6395	208 Liter Drum	1 Drum
ENGINE OILS	68218953GA	n/a	n/a	SAE 0W-20 MOPAR® ENGINE OIL, full synthetic	Rating: API SN, Energy Conserving, ILSAC GF-5. Contains special protective additives for superior engine protection. Approved to service all engines that require SAE 0W-20 engine oils.	MS-6395	1,008 x 0.946 Liter Pallet	1 Pallet
ENGINE OILS	68218954GA	n/a	n/a	SAE 0W-20 MOPAR® ENGINE OIL, full synthetic	Rating: API SN, Energy Conserving, ILSAC GF-5. Contains special protective additives for superior engine protection. Approved to service all engines that require SAE 0W-20 engine oils.	MS-6395	180 x 5 Liter Pallet	1 Pallet
ENGINE OILS	68171066GA	n/a	n/a	0W-40 MOPAR® ENGINE OIL, synthetic	Specifically formulated for the needs of Chrysler SRT engines where MS-12633 is required. It may also be used in SRT engines originally recommending Chrysler MS-10725	MS-12633	0.946 Liter Bottle	12 Bottles
ENGINE OILS	68171067GA	n/a	n/a	0W-40 MOPAR® ENGINE OIL, synthetic	Specifically formulated for the needs of Chrysler SRT engines where MS-12633 is required. It may also be used in SRT engines originally recommending Chrysler MS-10725	MS-12633	5 Liter Bottle	3 Bottles
ENGINE OILS	68218890GA	04761872MB	68066407EB	SAE 5W-20 MOPAR® ENGINE OIL	Rating API SM Energy Conserving, ILSAC GF-5 Specially developed with Chrysler engineering, this product exceeds requirements for API Certified SM engine oils.	MS-6395	0.946 Liter Bottle	12 Bottles
ENGINE OILS	68218891GA	68079549MB	68066408EB	SAE 5W-20 MOPAR® ENGINE OIL	Rating API SM Energy Conserving, ILSAC GF-5 Specially developed with Chrysler engineering, this product exceeds requirements for API Certified SM engine oils.	MS-6395	5 Liter Bottle	3 Bottles

Mopar International - Lubricant and Chemical Cross Reference Chart

Category	NEW Mopar International Part Number	Previous US Part Number	Previous International Part Number	Product	Product Description	MS-SPEC	Unit	MSQ
ENGINE OILS	68218892GA	68044413MB	68066415EB	SAE 5W-20 MOPAR® ENGINE OIL	Rating API SM Energy Conserving, ILSAC GF-5 Specially developed with Chrysler engineering, this product exceeds requirements for API Certified SM engine oils.	MS-6395	208 Liter Drum	1 Drum
ENGINE OILS	68218893GA	04762632MB	68080343EB	SAE 5W-20 MOPAR® ENGINE OIL	Rating API SM Energy Conserving, ILSAC GF-5 Specially developed with Chrysler engineering, this product exceeds requirements for API Certified SM engine oils.	MS-6395	1,008 x 0.946 Liter Pallet	1 Pallet
ENGINE OILS	68218894GA	68079672MB	68079672EA	SAE 5W-20 MOPAR® ENGINE OIL	Rating API SM Energy Conserving, ILSAC GF-5 Specially developed with Chrysler engineering, this product exceeds requirements for API Certified SM engine oils.	MS-6395	180 x 5 Liter Pallet	1 Pallet
ENGINE OILS	68218920GA	04761838MB	68066409EB	SAE 5W-30 MOPAR® ENGINE OIL	Rating: API SM / GF-5 Energy Conserving Approved to service all engines that require SAE 5W-30 engine oils in all climates. Suitable for use in gasoline, flexible fuel (E85) and turbo charged engines.	MS-6395	0.946 Liter Bottle	12 Bottles
ENGINE OILS	68218921GA	04761844MB	68066410EB	SAE 5W-30 MOPAR® ENGINE OIL	Rating: API SM / GF-5 Energy Conserving Approved to service all engines that require SAE 5W-30 engine oils in all climates. Suitable for use in gasoline, flexible fuel (E85) and turbo charged engines.	MS-6395	5 Liter Bottle	3 Bottles
ENGINE OILS	68218922GA	68044414MB	68066416EB	SAE 5W-30 MOPAR® ENGINE OIL	Rating: API SM / GF-5 Energy Conserving Approved to service all engines that require SAE 5W-30 engine oils in all climates. Suitable for use in gasoline, flexible fuel (E85) and turbo charged engines.	MS-6395	208 Liter Drum	1 Drum
ENGINE OILS	68218923GA	04762630MB	68080344EB	SAE 5W-30 MOPAR® ENGINE OIL	Rating: API SM / GF-5 Energy Conserving Approved to service all engines that require SAE 5W-30 engine oils in all climates. Suitable for use in gasoline, flexible fuel (E85) and turbo charged engines.	MS-6395	1,008 x 0.946 Liter Pallet	1 Pallet
ENGINE OILS	68218924GA	04762635MB	04762635EB	SAE 5W-30 MOPAR® ENGINE OIL	Rating: API SM / GF-5 Energy Conserving Approved to service all engines that require SAE 5W-30 engine oils in all climates. Suitable for use in gasoline, flexible fuel (E85) and turbo charged engines.	MS-6395	180 x 5 Liter Pallet	1 Pallet
ENGINE OILS	68231014GA	68001334PB	n/a	5W-30 MOPAR® ENGINE OIL, synthetic	Approved for 3.0L CRD (WK) OM642.	MS-11116 MB-229.51	0.946 Liter Bottle	12 Bottles
ENGINE OILS	68231015GA	n/a	n/a	5W-30 MOPAR® ENGINE OIL, synthetic	Approved for 3.0L CRD (WK) OM642.	MS-11116 MB-229.51	5 Liter Bottle	3 Bottles
ENGINE OILS	68231020GA	05127394PB	n/a	5W-40 MOPAR® ENGINE OIL, synthetic	Service Fill SRT8, 6.1L Service Fill SRT10, 8.3L, 8.4L Service Fill Crossfire & SRT6 Service Fill 2.8L diesel (KJ)	MS-10850	0.946 Liter Bottle	12 Bottles
ENGINE OILS	68231021GA	n/a	n/a	5W-40 MOPAR® ENGINE OIL, synthetic	Service Fill SRT8, 6.1L Service Fill SRT10, 8.3L, 8.4L Service Fill Crossfire & SRT6 Service Fill 2.8L diesel (KJ)	MS-10850	5 Liter Bottle	3 Bottles
ENGINE OILS	68218931GA	04761845MB	68066412EB	SAE 10W-30 MOPAR® ENGINE OIL	Rating: API SM, Energy Conserving, ILSAC GF-5 Approved to service all engines that require SAE 10W-30 engine oils in all climates. Suitable for use in both gasoline and flexible fuel engines.	MS-6395	5 Liter Bottle	3 Bottles
ENGINE OILS	68218932GA	68044416MB	68066417EB	SAE 10W-30 MOPAR® ENGINE OIL	Rating: API SM, Energy Conserving, ILSAC GF-5 Approved to service all engines that require SAE 10W-30 engine oils in all climates. Suitable for use in both gasoline and flexible fuel engines.	MS-6395	208 Liter Drum	1 Drum
ENGINE OILS	68218934GA	04762636MA	04762636EB	SAE 10W-30 MOPAR® ENGINE OIL	Rating: API SM, Energy Conserving, ILSAC GF-5 Approved to service all engines that require SAE 10W-30 engine oils in all climates. Suitable for use in both gasoline and flexible fuel engines.	MS-6395	180 x 5 Liter Pallet	1 Pallet
ENGINE OILS	68218933GA	04762631MB	68080345EB	SAE 10W-30 MOPAR® ENGINE OIL	Rating: API SM, Energy Conserving, ILSAC GF-5 Approved to service all engines that require SAE 10W-30 engine oils in all climates. Suitable for use in both gasoline and flexible fuel engines.	MS-6395	1,008 x 0.946 Liter Pallet	1 Pallet
ENGINE OILS	68218930GA	04761839MB	68066411EB	SAE 10W-30 MOPAR® ENGINE OIL	Rating: API SM, Energy Conserving, ILSAC GF-5 Approved to service all engines that require SAE 10W-30 engine oils in all climates. Suitable for use in both gasoline and flexible fuel engines.	MS-6395	0.946 Liter Bottle	12 Bottles
ENGINE OILS	68218943GA	68024968MA	n/a	SAE 15W-40 MOPAR® ENGINE OIL	Rating: API CJ-4/CI-4+ 6700 CJ-4 rated for Dodge truck with low emissions 6.7L Cummins turbo diesel engine. Approved for 5.9L Cummins diesels operating on low or high sulfur fuel.	MS-10902	1,008 x 0.946 Liter Pallet	1 Pallet
ENGINE OILS	68218940GA	68024966MA	n/a	SAE 15W-40 MOPAR® ENGINE OIL	Rating: API CJ-4/CI-4+ 6700 CJ-4 rated for Dodge truck with low emissions 6.7L Cummins turbo diesel engine. Approved for 5.9L Cummins diesels operating on low or high sulfur fuel.	MS-10902	0.946 Liter Bottle	12 Bottles

Mopar International - Lubricant and Chemical Cross Reference Chart

Category	NEW Mopar International Part Number	Previous US Part Number	Previous International Part Number	Product	Product Description	MS-SPEC	Unit	MSQ
GEAR AND AXLE LUBRICANTS	68218041GA	04874468	05103530EA	GEAR & AXLE LUBRICANT SAE 80W-90	General purpose GL-5 gear lube. Use in rear axles as specified. Excellent wear and noise protection.	MS-9020	0.946 Liter Bottle (Yorker Top)	12 Bottles
GEAR AND AXLE LUBRICANTS	68218657GA	04874469	05103526EA	SYNTHETIC GEAR & AXLE LUBRICANT SAE 75W-140	High-performance synthetic GL-5 gear lube. Also highly recommended for LX body rear axle. Recommended for trailer tow and heavy-duty, high-load vehicles.	MS-8985	0.946 Liter Bottle (Yorker Top)	12 Bottles
GEAR AND AXLE LUBRICANTS	68218655GA	05010320AA	05103529EA	SYNTHETIC GEAR LUBRICANT SAE 75W-90	Specifically formulated for improved fuel efficiency while providing exceptional antiwear properties. For use in all Chrysler — USA Corporate axles.	MS-9763	0.946 Liter Bottle (Yorker Top)	12 Bottles
GEAR AND AXLE LUBRICANTS	05136035GB	05136035AB	n/a	SYNTHETIC AXLE LUBRICANT SAE 75W-85	This fully synthetic GL-5 fluid is intended for use only in the Chrysler Crossfire axle assembly. Not intended for use in other Chrysler Group LLC vehicles.		0.946 Liter Bottle	12 Bottles
GEAR AND AXLE LUBRICANTS	05016796GC	05016796AC	05016796EB	TRANSFER CASE LUBRICANT NV247	Used for the NV247/NV249 Transfer Cases		0.946 Liter Bottle	12 Bottles
GEAR AND AXLE LUBRICANTS	68218655GA	68218655AA	n/a	SYNTHETIC GEAR LUBRICANT SAE 75W-90	Specifically formulated for improved fuel efficiency while providing exceptional antiwear properties. For use in all Chrysler — USA Corporate axles.	MS-9763	0.946 Liter Bottle	12 Bottles
LUBRICANTS and GREASE	68194558GA	68194558AA	n/a	HALF SHAFT GREASE	Half Shaft Grease for the Fiat 500		140 g Tube	1 Tube
POWER STEERING and BRAKE FLUIDS	04318080GC	04318080AC	n/a	BRAKE FLUID DOT 3 MOTOR VEHICLE	For use in hydraulic brake systems specifying DOT 3 brake fluid or disc or drum brakes. Meets or exceeds SAE and federal specifications.	MS-4574	0.355 Liter Bottle	12 Bottles
POWER STEERING and BRAKE FLUIDS	04549625GD	04549625AD	68078179EA	BRAKE & CLUTCH FLUID DOT 4 MOTOR VEHICLE	Specially blended to withstand heat and pressure. DOT 4 fluid meets all DOT requirements for DOT 4.	MS-9971	0.355 Liter Bottle	12 Bottles
POWER STEERING AND BRAKE FLUIDS	68218064GA	05166226AA	n/a	POWER STEERING FLUID +4	Convenient, easy-to-pour, pint-sized container. Meets Chrysler material specification for post 1998 Chrysler power steering systems that require MS-9602 fluid. Compatible with ATF+4.	MS-9602	0.946 Liter Bottle	12 Bottles
POWER STEERING AND BRAKE FLUIDS	68234631GA	05142893AA	05142893EA	HYDRAULIC SYSTEM POWER STEERING FLUID	Specifically developed for WK hydraulic/ power steering systems.	MS-10838	0.946 Liter Bottle	12 Bottles
TECH TOOLS	05010884GC	05010884AC	05103523EB	ATF-RTV	Silicone Rubber RTV developed specifically to retain sealing and adhesion properties when exposed to automatic transmission fluid.	MS-GF41B	85 g Tube	12 Tubes
TECH TOOLS	04883971GB	04883971AB	n/a	ENGINE SEALANT RTV Silicone Rubber Adhesive	Use to seal components exposed to engine oil. Specifically designed black silicone rubber RTV retains adhesion and sealing properties when exposed to engine oil.	MS-GF44B	85 g Tube	12 Tubes
TECH TOOLS	05013477GC	05013477AC	05013477AA	AXLE RTV	The only RTV Sealer approved for use in Chrysler built axles using Mopar SAE 75W-90 Axle Lubricant P/N 05010320AA. This is the only factory used sealer compatible for use with this lubricant.	MS-GF46	85 g Tube	12 Tubes
TECH TOOLS	68065196GA	68065196AA	04897150EA	BRAKE PARTS CLEANER NON-CHLORINATED	Removes oil, grease and brake fluid residue from all metal brake parts. Loosens brake dust for easy removal.		425 g Aerosol Can	12 Cans
TECH TOOLS	82300234GB	82300234	n/a	SILICONE RUBBER RTV	Silicone Rubber RTV developed specifically to be engine oil, gear lubricant and coolant compatible. Excellent adhesion, even on oily surfaces. Withstands temperatures to 635°F (330°C).	MS-GF44d	85 g Tube	12 Tubes