

COMPANY NAME : ООО "Юниджет"

CUSTOMER EQUIP NUM :

COMPARTMENT NAME : Новое масло

SERIAL NUMBER : UNIJETNEOIL

MANUFACTURER :

MODEL :

JOB SITE :

EXT WARR NUMBER:

SHOP JOB NUM :

COMP SERIAL NUM :

COMPARTMENT MODEL :

COMP MANUFACTURER :

SAMPLE LABEL NUM : образец 1, 0W-30, новое

FLUID BRAND/WEIGHT : OTHER/0W-30

FLUID TYPE : BMW Twin Power Turbo SAE 0W-30 LL-04

EXT WARR EXPIRE DATE:

FAX:

PHONE:

SAMPLE TYPE: OIL

SAMPLE SHIP TIME (days): 1

143441, Московская область, г.о. Красногорск, д. Путилково, тер. Гринвуд, стр. 31/1

+7 (495) 970-79-36

Z

LAB

LAB CONTROL NUMBER	SAMPLE DATE	PROCESS DATE	EQUIPMENT METER	METER ON FLUID	FLUID CHANGED	MAKE UP FLUID	MAKE UP FLUID UNITS	FILTER CHANGED
V27U-55140-0032	19.05.2025	20.05.2025	0 HR	0 HR	U	0.0	L	U
No Action Required	Кислотное число масла (TAN) - 1,67 мг KOH/г. Вязкость при 40°C - 60,52 сСт. Индекс вязкости - 194. Содержание продуктов износа и показатели состояния масла в норме. Признаков попадания загрязнений не обнаружено. В настоящее время проблем, согласно пробе, нет. Продолжайте отбор образцов, согласно графику.							

Wear Metals (ppm)	Cu	Fe	Cr	Al	Pb	Sn	Si	Na	K	B	Mo	Ni	Ag	Ti	V	Sb	Cd	Ca	Mg	Zn	P	Ba
V27U-55140-0032	0	0	0	0	0	0	7	0	1	136	68	0	0	0	0	0	0	1628	14	682	726	0

OIL Condition / Particle Count (ct/ml)	ST	OXI	NIT	SUL	W	A	F	PFC	V100	TBN	ISO
V27U-55140-0032	0	12	4	19	None	N	N	N	11.75	8.7	N

Ag = Silver, Al = Aluminum, B = Boron, Ca = Calcium, Cr = Chromium, Cu = Copper, Fe = Iron, P = Phosphorus, K = Potassium, Mg = Magnesium, Mo = Molybdenum, Na = Sodium, Ni = Nickel, Pb = Lead, Si = Silicon, Sn = Tin, V = Vanadium, Zn = Zinc  
A = Antifreeze, F = Fuel, W = Water, P = Positive, N = Negative, T = Trace, E = Excessive, NIT = Nitration, OXI = Oxidation, ST = Soot, SUL = Sulfation, ISO = ISO Rating, PFC = Percent Fuel Content, PQI = Particle Quantifying index  
NaW = Salt Water, FL Pt = Flash Point, TAN = Total Acid Number, TBN = Total Base Number, H2O = Karl Fisher result, V100 = Viscosity@100C, V40 = Viscosity@40C, FDM = Ferrous Debris Monitor  
Notice: This analysis is intended as an aid in predicting mechanical wear. No guarantee, expressed or implied, is made against failure of this piece of equipment or a component thereof.

COMPANY NAME : ООО "Юниджет"

CUSTOMER EQUIP NUM :

COMPARTMENT NAME : Новое масло

SERIAL NUMBER : UNIJETNEWOIL

MANUFACTURER :

MODEL :

JOB SITE :

EXT WARR NUMBER:

SHOP JOB NUM :

COMP SERIAL NUM :

COMPARTMENT MODEL :

COMP MANUFACTURER :

SAMPLE LABEL NUM : образец 2, 5W-30, новое

FLUID BRAND/WEIGHT : OTHER/5W-30

FLUID TYPE : BMW Twin Power Turbo SAE 5W-30 LL-04

EXT WARR EXPIRE DATE:

FAX:


PHONE:

SAMPLE TYPE: OIL

SAMPLE SHIP TIME (days): 1

143441, Московская область, г.о. Красногорск, д. Путилково, тер. Гринвуд, стр. 31/1

+7 (495) 970-79-36



LAB CONTROL NUMBER	SAMPLE DATE	PROCESS DATE	EQUIPMENT METER	METER ON FLUID	FLUID CHANGED	MAKE UP FLUID	MAKE UP FLUID UNITS	FILTER CHANGED
V27U-55140-0033	19.05.2025	20.05.2025	0 HR	0 HR	U	0.0	L	U
No Action Required	Кислотное число масла (TAN) - 3,18 мг KOH/г. Вязкость при 40°C - 65,05 сСт. Индекс вязкости - 178. Содержание продуктов износа и показатели состояния масла в норме. Признаков попадания загрязнений не обнаружено. В настоящее время проблем, согласно пробе, нет. Продолжайте отбор образцов, согласно графику.							

Wear Metals (ppm)	Cu	Fe	Cr	Al	Pb	Sn	Si	Na	K	B	Mo	Ni	Ag	Ti	V	Sb	Cd	Ca	Mg	Zn	P	Ba
V27U-55140-0033	0	1	0	0	0	0	4	1	0	72	0	0	0	0	0	0	0	1569	7	730	783	0

OIL Condition / Particle Count (ct/ml)	ST	OXI	NIT	SUL	W	A	F	PFC	V100	TBN	ISO
V27U-55140-0033	0	7	6	13	None	N	N	N	11.74	9.4	N

Ag = Silver, Al = Aluminum, B = Boron, Ca = Calcium, Cr = Chromium, Cu = Copper, Fe = Iron, P = Phosphorus, K = Potassium, Mg = Magnesium, Mo = Molybdenum, Na = Sodium, Ni = Nickel, Pb = Lead, Si = Silicon, Sn = Tin, V = Vanadium, Zn = Zinc  
A = Antifreeze, F = Fuel, W = Water, P = Positive, N = Negative, T = Trace, E = Excessive, NIT = Nitration, OXI = Oxidation, ST = Soot, SUL = Sulfation, ISO = ISO Rating, PFC = Percent Fuel Content, PQI = Particle Quantifying index  
NaW = Salt Water, FL Pt = Flash Point, TAN = Total Acid Number, TBN = Total Base Number, H2O = Karl Fisher result, V100 = Viscosity@100C, V40 = Viscosity@40C, FDM = Ferrous Debris Monitor  
Notice: This analysis is intended as an aid in predicting mechanical wear. No guarantee, expressed or implied, is made against failure of this piece of equipment or a component thereof.